





Electric ranges

- ◆ Hot plates with protectors which automatically cut down power level by approx. 50% when not in use.
- ◆ 7 position switch for accurate temperature regulation.
- ◆ Space between hot plates less than 35mm making moving of heavy cookware much easier.
- ◆ Oven made of chrome nickel steel.





ELECTRIC RANGE WITH 2 HOT PLATES

Model No:	2023201
Dimensions:	400 x 850 x 700 mm corpus height
Description:	– 2 hot plates with edge, 1 x 2,5 and 1 x 4,0 kW, 300 x 300 mm each – Housing made completely of chrome nickel steel (1.4301) / (304) – Tightly welded top plate with lateral drain channels for easy cleaning.
Electrical equipment:	7 position switch, hot plates with protector 300 x 300 mm, mains connection, IPX5.
Connected load:	6,5 kW 3 NPE AC 400V
Heat emission:	sensitive: 1300 W latent: 520 W





ELECTRIC RANGE WITH 4 HOT PLATES

Model No:	2023202
Dimensions:	800 x 850 x 700 mm corpus height
Description:	– 4 hot plates with edge, 2 x 2, 5 and 2 x 4,0 kW, 300 x 300 mm each – Housing made completely of chrome nickel steel (1.4301) / (304) – Tightly welded top plate with lateral drain channels for easy cleaning.
Electrical equipment:	7 position switch, hot plates with protector 300 x 300 mm, mains connection, IPX5.
Connected load:	13 kW 3 NPE AC 400V
Heat emission:	sensitive: 2600 W latent: 1040 W





ELECTRIC RANGE WITH 4 HOT PLATES AND ELECTRIC OVEN 2/1 GN

Model No:	2023203
Dimensions:	800 x 850 mm, 700 mm corpus height
Description:	- hot plates with edge, 2 x 2,5 and 2 x 4,0 kW, 300 x 300 mm each. - Oven 5,4 kW - Housing made completely of chrome nickel steel (1.4301) / (304) - Tightly welded top plate with lateral drain channels for easy cleaning.
Electrical equipment:	7 position switch, hot plates with protector, mains connection, IPX5.
Electric oven:	535 x 670 x 250 mm
Connected load:	Direct upper heat, indirect lower heat, 50-300°C
Electrical equipment:	5,4 kW 2 NPE AC 400V
Accessories:	Internal tubular heating element for upper heat. Indirect lower heat controllable by a thermostat, with control lamp, control switch and safety temperature thermostat.
Connected load:	18,4 kW 3 NPE AC 400V
Heat emission:	1 baking tray 2/1 GN, 1 CNS grid 2/1 GN
Optional accessoires:	sensitive: 4490 W latent: 1904 W 206 103 CNS oven grid 2/1GN 202 112 Baking tray2/1GN



ELECTRIC RANGE WITH 6 HOT PLATES

Model No:	2023204
Dimensions:	1200 x 850 mm, 700 mm corpus height
Description:	- hot plates with edge, 4 x 2,5 and 2 x 4,0 kW, 300 x 300 mm each - Housing made completely of chrome nickel steel (1.4301) / (304) - Tightly welded top plate with lateral drain channels for easy cleaning.
Electrical equipment:	7 position switch, hot plates with protector, mains connection, IPX5.
Connected load:	18kW 3 NPE AC 400V
Heat emission:	sensitive: 3600W latent: 1440W



ELECTRIC RANGE WITH 6 HOT PLATES AND ELECTRIC OVEN 2/1 GN

Model No:	2023205
Dimensions:	1200 x 850 mm, 700 mm corpus height
Description:	- hot plates with edge, 4 x 2,5 and 2 x 4,0 kW, 300 x 300 mm each. - Oven 5,4 kW - Housing made completely of chrome nickel steel (1.4301) / (304) - Tightly welded top plate with lateral drain channels for easy cleaning.
Electrical equipment:	7 position switch, hot plates with protector, mains connection, IPX5.
Electric oven:	535 x 670 x 250 mm
Connected load:	Direct upper heat, indirect lower heat, 50-300°C
Electrical equipment:	5, 4 kW 2 NPE AC 400V
Accessories:	Internal tubular heating element for upper heat. Indirect lower heat controllable by a thermostat, with control lamp, control switch and safety temperature thermostat.
Connected load:	1 baking tray 2/1 GN, 1 CNS grid 2/1 GN
Heat emission:	23,4 kW 3 NPE AC 400V
Optional accessoires:	sensitive: 5490 W latent: 2304 W
	206 103 CNS oven grid 2/1GN 202 112 Baking tray2/1GN 845 756 1 heated cupboard including wing door