

## SA 3370



Control terminal with drip-proof foil keyboard



Freely accessible surfaces everywhere – even on the rear blade surface



Can be switched to manual mode



Slice thickness control knob for precise adjustment from 0 - 24 mm



Closed rubber frame

### Automatic slicer in perfection

The gravity slice with automatic carriage drive is ideal for all applications in which large quantities of product need to be sliced and need to comply with requirements for a decorative tray. Regardless of which items need to be sliced – the SA 3370 impresses with its simple operation, fastest possible slicing processes, excellent slicing results with the simplest possible cleaning.

### BENEFITS

- Smooth, freely accessible surfaces everywhere in high-grade anodic design, Machine base anneal-lacquered
- Closed blade cover plate  
No offset
- Low layout for ideal insertion of the slicing items on the carriage
- Special high-performance blade Ø 330 mm, hard-chromium plated - for long edge retention and high slicing power
- High product retaining bar and patented, comb-like food holder
- High-torque, smooth-running blade motor, double ball-bearing supported with 450 watts for ideal traction even with difficult slicing items  
Air cooling system to prevent the housing and blade from heat build-up
- Generously-sized automatic drive – can be switched to manual drive – carriage (340 mm wide) for product sizes of Ø 244 mm round and 300 x 244 mm / rectangular
- Orderly, easily accessible control terminal with drip-proof foil keyboard
- Precisely machined guide grooves in limit and blade cover plate for superior gliding attributes
- Slice thickness setting for simple and precise
- slice thickness adjustment, 0 – 24 mm


### ACCESSORIES

- Special oil
- 2-disc blade sharpener

### TECHNICAL DATA

Product no.	SA 3370	
Motor power	450 watts	230 V~ alternating or 400 V~ three-phase current
Blade (Ø mm)	Ø 330 mm, smooth, solid steel blade	
Blade speed	229/rpm	
Slices per minute max.	max. 80	
Slice thickness min. - max. (mm)	0 – 24 mm	
Emission noise level	< 69 dBA	
Slicing speed	up to 80 strokes / min.	
Slice size (L x H mm)	280 x 210 mm	
Slice dimension (L x W mm)	280 x 260 mm	
Footprint (L x W mm)	540 x 440 mm	
Exterior dimensions (L x W x H)	695 x 505 x 490 mm	
Workspace (L x W x H)	855 x 640 x 585 mm	
Net weight	50 kg	
Operating period	Continuous duty	
Warranty	1 year	





Generously-sized carriage,  
can be folded for cleaning



## COMFORTABLE CONTROL DISPLAY



**Red and green keys** On and off switch for the blade motor.

**Yellow key** On and off switch for the carriage automatic system.

**Select number of slices with + keys**  
When the quantity is reached, the carriage returns to the home position and ends the slicing process.

No selection of the number of slices; the machine counts the slices in increments.

## Automatic size detection

The first time the carriage is advanced, the machine measures the length of the product to be sliced and then sets the stroke to be driven. That facilitates the fastest possible total speed – with short strokes up to 80 strokes/min.

With L key, the stroke length can also be manually set – short 140 mm, medium 240 mm, long 340 mm.

With the S key, the stroke speed can be preset.