

EURO 3310 DS



Piezo switch engineering, safe, water-tight and indestructible



Surrounding rubber frame



Ball-bearing supported, internal feed carriage for simple slicing product advance



A meat cutter, you can put big pieces on and think highly of.

The long slicing length of 300 mm means even fresh meats like top sides do not pose any problem while processing.

BENEFITS

- Special high-performance blade Ø 330 mm hard-chromium plated
- Internal blade cover plate
- High-torque, smooth-running motor, double ball-bearing support with 500 watts for ideal traction even with difficult slicing items
- Air cooling system to prevent the housing and blade from heat build-up
- Piezo switch engineering
- Generously sized, smooth-running carriage with internal ball-bearing supported interior carriage (slice length: 300 mm), can be removed for cleaning
- Precisely machined guide grooves in limit and blade cover plate for superior gliding attributes
- Closed base plate
- Slice product support
- Slicing thickness 0 – 24 mm



TECHNICAL DATA

Product no.	EURO 3310 DS	
Motor power	500 watts	230 V~ alternating or 400 V~ three-phase current
Blade (Ø mm)	Ø 330 mm, smooth, solid steel blade	
Blade speed	230/rpm	
Slice thickness max.	24 mm	
Emission noise level	< 69 dBA	
Slice size (L x H mm)	300 x 223 mm	
Slice dimension (L x W mm)	300 x 340 mm	
Footprint (L x W mm)	540 x 440 mm	
Exterior dimensions (L x W x H)	650 x 605 x 445 mm	
Workspace (L x W x H)	740 x 690 x 600 mm	
Net weight	41.2 kg	
Operating period	Continuous duty	
Warranty	2 years	

ACCESSORIES

- Special oil
- 2-disc blade sharpener

OPTION



Blade in non-stick version

